



## INSTALLS WHITE, STAYS WHITE

## **Radon Mitigation Fan**

All RadonAway® fans are specifically designed for radon mitigation. RP Series Fans provide superb performance, run ultra-quiet and are attractive. They are ideal for most sub-slab radon mitigation systems.

## **Features**

- NEW Stay-White<sup>™</sup> housing
- · Energy efficient
- RP140 ENERGY STAR Most Efficient 2018
- Ultra-quiet operation
- Meets all electrical code requirements
- Water-hardened motorized impeller
- Seams sealed to inhibit radon leakage (RP140 & RP145 double snap sealed)
- ETL Listed for indoor or outdoor use
- Thermally protected motor
- · Rated for commercial and residential use

MODEL	D/N	FAN DUCT	WATTS	RECOM. MAX. OP. PRESSURE "WC	TYPICAL CFM vs. STATIC PRESSURE WC				
MODEL	P/N	DIAMETER			0"	.5"	1.0"	1.5"	2.0"
RP140	28460	4"	15-21	0.7	135	70	-	-	-
RP145	28461	4"	41-72	1.7	166	126	82	41	3
RP260	28462	6"	47-65	1.3	251	157	70	-	-
RP265	28463	6"	95-139	2.3	375	282	204	140	70
RP380*	28208	8"	96-138	2.0	531	415	268	139	41

<sup>\*</sup>Currently not stay-white material.




with U.S. and imported parts.





All RadonAway® inline radon fans are covered by our 5-year, hassle-free warranty.





Model	Α	В	С
RP140	4.5"	9.7"	8.5"
RP145	4.5"	9.7"	8.5"
RP260	6"	11.75"	8.6"
RP265	6"	11.75"	8.6"
RP380	8"	13.41"	10.53"

For Further Information, Contact Your Radon Professional

© 2018 RadonAway Rev B 0618

P/N 02051