

RPc Series




Radon Mitigation Fan

All RadonAway[®] fans are specifically designed for radon mitigation. RPc Series Fans provide superb performance, run ultra-quiet and are attractive. They are ideal for most sub-slab radon mitigation systems.

Features

- Energy efficient
- Ultra-quiet operation
- Meets all electrical code requirements
- Water-hardened motorized impeller
- Seams sealed to inhibit radon leakage (RP140c & RP145c double snap sealed)
- ETL Listed for indoor or outdoor use
- Thermally protected motor
- Rated for commercial and residential use

MODEL	P/N	FAN DUCT DIAMETER	WATTS	RECOM. MAX. OP. PRESSURE "WC	TYPICAL CFM vs. STATIC PRESSURE WC				
MODEL					0"	.5"	1.0"	1.5"	2.0"
RP140c*	23029-1	4"	15-21	0.7	135	70	-	-	-
RP145c	23030-1	4"	41-72	1.7	166	126	82	41	3
RP260c	23032-1	6"	47-65	1.3	251	157	70	-	-
RP265c	23033-1	6"	91-129	2.2	334	247	176	116	52
RP380	28208	8"	95-152	2.0	497	353	220	130	38





Made in USA with U.S. and imported parts.

All RadonAway[®] inline radon fans are covered by our 5-year, hassle-free warranty.



A									
Α	В	С							
4.5"	9.7"	8.5"							
4.5"	9.7"	8.5"							
6"	11.75"	8.6"							
6"	11.75"	8.6"							
8"	13.41"	10.53"							
	A 4.5" 4.5" 6" 6"	A B 4.5" 9.7" 4.5" 9.7" 6" 11.75" 6" 11.75"							

For Further Information Contact Your Radon Professional: