



DUCT BOOST

INCREASE AIR FLOW AND HEATING EFFICIENCY.

There is a solution to efficiently move air in your ducting.

Adding a Spruce inline auxiliary fan to a heating system with long duct runs or multiple bends boosts system capacity and conserves energy. Five kits are available, offering two fan options and up to three switch choices: pressure sensing, current sensing, and pressure sensing with timer.

MADE IN USA Made in USA with U.S. and imported parts.

ETL ETL Listed
Intertek

5 YEAR WARRANTY All Spruce™ inline fans are covered by our 5-year, hassle-free warranty.

Duct Boost Kit Features

- RB110 EnergyStar® Rated or RB190 inline fan
- Five-year warranty
- Quiet and effective
- Energy efficient
- HVI certified fan performance



SDB110P Kit



DUCT BOOSTING TECHNICAL SPECIFICATIONS

Fan Specifications

TYPICAL CFM VS. STATIC PRESSURE										
MODEL	P/N	DUCT	WATTS	0"	0.2"	0.5"	0.75"	1"	1.25"	1.5"
SDB110P	28131	4"	14-18	125	100*	60*	1	-	-	-
SDB110C	28259	4"	14-18	125	100*	60*	1	-	-	-
SDB190P	28575	4"	45-62	158	140*	114	93	73	53	33
SDB190C	28576	4"	45-62	158	140*	114	93	73	53	33
SDB190T	28577	4"	45-62	158	140*	114	93	73	53	33

*HVI Certified Values

SWITCH TYPE	KIT	P/N	KIT CONTENTS
	SDB110P	28131	<ul style="list-style-type: none"> RB110† fan Mounting bracket Air pressure-sensing switch Probe Vinyl tubing
	SDB110C	28259	<ul style="list-style-type: none"> RB110† fan Mounting bracket A/C current-sensing switch
	SDB190P	28575	<ul style="list-style-type: none"> RB190 fan Mounting bracket Air pressure-sensing switch Probe Vinyl tubing
	SDB190C	28576	<ul style="list-style-type: none"> RB190 fan Mounting bracket A/C current-sensing switch
	SDB190T	28577	<ul style="list-style-type: none"> RB190 fan Mounting bracket Air pressure-sensing switch Probe Vinyl tubing Timer with time-delay option



Spruce RB110



Made in USA with U.S. and imported parts.



ETL Listed

Intertek



All Spruce™ inline fans are covered by our 5-year, hassle-free warranty.



Duct Boost Fan Plastic Housing Dimensions

MODEL	H	h	D	d
RB110†	8.5"	1"	9.7"	4"
RB190	8.5"	1"	9.7"	4"

†Energy Star® rated.

