



۲

## INSTALLS WHITE, STAYS WHITE

## **Radon Mitigation Fan**

All RadonAway<sup>®</sup> fans are specifically designed for radon mitigation. GP Series Fans offer a wide range of performance options that make them ideal for most sub-slab radon mitigation systems.

## **Features**

- NEW Stay-White<sup>™</sup> housing
- Quiet operation

( )

- Water-hardened motor
- · Seams sealed under negative pressure (to inhibit radon leakage)
- Mounts on duct pipe or with integral flange
- 3" diameter ducts for use with 3" or 4" pipe
- Electrical box for hard wire or plug in
- ETL Listed for indoor or outdoor use
- 4 interchangeable GP models

	MODEL	D/N	FAN DUCT	WALLS	RECOM. MAX. OP. PRESSURE "WC	TYPICAL CFM vs. STATIC PRESSURE WC						
	MODEL	P/N	DIAMETER			1.0"	1.5"	2.0"	2.5"	3.0"	3.5"	4.0"
	GP201	28465	3"	31-67	1.8	54	42	-	-	-	-	-
	GP301	28466	3"	56-100	2.3	64	54	41	-	-	-	-
	GP401	28467	3"	62-128	3.0	-	61	52	44	22	-	-
	GP501	28468	3"	68-146	3.8	-	-	66	58	50	27	-

MADE IN Made in USA with U.S. and imported parts.

ETL Listed

hassle-free warranty

All RadonAway® inline radon fans are covered by our 5-year,

For Further Information, Contact Your Radon Professional:



Rev B 0719 P/N 02045

© 2019 RadonAway

GPSW-cutsheet-0719CH.indd 1

12.5"

۲